

Concrete Bell & Spigot Pipe

Rubber Gasketed

Inside Diameter	Weight (lb. per ft.)	Approximate Lay Length	ASTM C-14	ASTM C-76			Notes
			Class 3	Class III	Class IV	Class V	
6"	37	3'	✓				<ul style="list-style-type: none"> • Available air tested for sanitary sewer, as required by ASTM specifications • Available reinforced and non-reinforced • We supply custom items, including bends, tees, wyes, and bevel ends. Please call for availability and lead time. • 3 - 4 week minimum lead time required for all pipe orders. Longer lead time may be necessary for pipe with an inside diameter of 30" or larger.
6"	37	3.5'	✓				
8"	52	3.5'	✓				
8"	52	4'	✓				
10"	88	3.5'	✓		✓	✓	
10"	88	7.5'	✓		✓	✓	
12"	120	8'	✓		✓	✓	
15"	154	8'	✓		✓	✓	
18"	201	8'	✓	✓	✓	✓	
21"	253	8'	✓	✓	✓	✓	
24"	392	8'	✓	✓	✓	✓	
27"	447	8'	✓	✓	✓	✓	
30"	534	8'	✓	✓	✓	✓	
36"	702	8'	✓	✓	✓	✓	
42"	889	8'		✓	✓	✓	
48"	1102	8'		✓	✓	✓	
54"	1139	8'		✓	✓		
60"	1351	8'		✓	✓		
66"	1587	8'		✓	✓		
72"	1880	8'		✓	✓		
84"	2560	8'		✓	✓		
96"	3111	10'		✓	✓		



GRANITE

PRECASTING & CONCRETE INC.